



- 5 ■ SPECIFICATIONS
- Current Rating : 2A AC/DC
 - Current Rating : 125V AC/DC
 - Withstanding Voltage : 1,000V AC/minute
 - Insulation Resistance : 1,000MΩ min.
 - Temperature Range :
 - Nylon 6T:- 40°C to + 105°C
 - PBT:- 25°C to + 85°C
 - Contact Resistance : 20mΩ max.
- PIN HEADER
- Part No. : JS-1127WS-XXx2(XXXX)
 - Product Code
 - ①Poles No: 02x2~40x2
 - ②Base:
 - Blank:PBT
 - 6T:Nylon 6T UL94V-0
- 4 6TNH:Nylon6T-66 UL94V-0;Non-Halogen
- Material : Base : Refer The Above Option
 - Contact : Brass, Gold Plated
 - Q'ty : 1,000 pcs./Bag

3

Poles	Dimension(mm)		Poles	Dimension(mm)	
	A	B		A	B
4	2.00	4.00	44	42.00	44.00
6	4.00	6.00	46	44.00	46.00
8	6.00	8.00	48	46.00	48.00
10	8.00	10.00	50	48.00	50.00
12	10.00	12.00	52	50.00	52.00
14	12.00	14.00	54	52.00	54.00
16	14.00	16.00	56	54.00	56.00
18	16.00	18.00	58	56.00	58.00
20	18.00	20.00	60	58.00	60.00
22	20.00	22.00	62	60.00	62.00
24	22.00	24.00	64	62.00	64.00
26	24.00	26.00	66	64.00	66.00
28	26.00	28.00	68	66.00	68.00
30	28.00	30.00	70	68.00	70.00
32	30.00	32.00	72	70.00	72.00
34	32.00	34.00	74	72.00	74.00
36	34.00	36.00	76	74.00	76.00
38	36.00	38.00	78	76.00	78.00
40	38.00	40.00	80	78.00	80.00
42	40.00	42.00			

 喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-1127WS-XXx2(XXXX)

2.0mm Disconnectable crimp style Pin Header

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	△	變更原因遺失	XXX	XX/XX/XX	△			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△	修改B點尺寸公差	黃科源	2008/07/09	△			
周慈雲		a7	.000 ±0.10	△	修改尺寸表	黃科源	2009/03/24	△			
DRAWN BY	DATE	SIZE	ANGLE		增加函索選項	林謙豪	2012/04/24	CUSTOMER			
吳弘文	2015/10/22	A4	0° ±1°	△	修改額定電流額定電壓	張逸維	2012/07/17				
			0° ±	△	增加Pin 2,3,4 標示	吳弘文	2013/10/04	Conforms to The RoHS Instruction			
			SHEET 1/1	△	修正圖框產品名稱	吳弘文	2015/10/22				