



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ HOUSING

- Part No. : JS-1136-XX
- Code No. ①
- ① Poles : 2 - 15
- Material : Nylon 66 UL94V-2
- Q' ty: 1,000 pcs./Bag

Poles	Dimensions(mm)	
	A	B
2	2.50	5.80
3	5.00	8.30
4	7.50	10.80
5	10.00	13.30
6	12.50	15.80
7	15.00	18.30
8	17.50	20.80
9	20.00	23.30
10	22.50	25.80
11	25.00	28.30
12	27.50	30.80
13	30.00	33.30
14	32.50	35.80
15	35.00	38.30



喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	△	ECR 200810-005	資料源	2008/10/22	△			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△	更正三角記號位置, 尺寸依實物修正	吳弘文	2013/09/23	△			
周慈雲		a3	.000 ±0.10	△	修定05, 07P B尺寸	吳弘文	2014/09/16	△			
DRAWN BY	DATE	SIZE	ANGLE						CUSTOMER		
吳弘文	2014/09/16	A4	0° ±1°	△					Conforms to The RoHS Instruction		
			.0° ±	△							
			SHEET 1/1	△							

PART NO JS-1136-XX

2.50mm Crimp Style Connectors Housing