



- SPECIFICATIONS
- Current Rating : 3A AC/DC
 - Withstanding Voltage : 1,000V AC/minute
 - Insulation Resistance : 1,000MΩ min.
 - Temperature Range : - 25°C to + 85°C
 - Contact Resistance : 20mΩ max.

- WAFER
- Part No. : JS-1143-XX (XX XX XX) ① ② ③ ④
 - ① Poles: 2-16PIN
 - ② Material: Blank : PBT UL94V-0
V0 : PA66 UL94V-0
 - ③ Plated: Blank : Gold Flash Plated.
T : Tin Plated
 - ④ DIP Length: Blank: DIP=3.4mm
D: DIP=3.0mm
 - Q' ty : 1,000 Pcs/Tube Packing

Poles	Dimensions(mm)			
	A	B	C	D
2	2.54	7.62	5.60	—
3	5.08	10.16	8.14	—
4	7.62	12.70	10.68	5.08
5	10.16	15.24	13.22	7.62
6	12.70	17.78	15.76	10.16
7	15.24	20.32	18.30	12.70
8	17.78	22.86	20.84	15.24
9	20.32	25.40	23.38	17.78
10	22.86	27.94	25.92	20.32
11	25.40	30.48	28.46	22.86
12	27.94	33.02	31.00	25.40
13	30.48	35.56	33.54	27.94
14	33.02	38.10	36.08	30.48
15	35.56	40.64	38.62	33.02
16	38.10	43.18	41.16	35.56
17	40.64	45.72	43.70	38.10
18	43.18	48.26	46.24	40.64

 喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞	1:1	mm	.0 ±0.30	△	RoHS compliant		07-01-03	△	修正敘述	吳弘文	15-04-15
CHECKED BY	PROJ	VER NO.	.00 ±0.25	△	200705-018		07-05-28	△			
周慈雲	⊕	a8	.000 ±0.10	△	200803-022		08-03-20	△			
DRAWN BY	DATE	SIZE	ANGLE		200809-009		08-09-10				
吳弘文	2015/05/15	A4	0° ±1°	△	201108-001 圖面整理	周美麗	11-08-08		CUSTOMER		
			.0° ±	△	新增規格	周美麗	13-01-28		Conforms to The RoHS Instruction		
			SHEET 1/1	△	修改鍍層編碼	張逸維	13-03-14				

PART NO JS-1143-XX
2.54mm Crimp Style Connectors Wafer