



■ SPECIFICATIONS

- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max

■ WAFER

• Part No. : JS-6001-XX X (XX XX XX XX)XX
 ① ② ③ ④ ⑤ ⑥ ⑦

Product Code

① Poles NO:02~15

② Structure

S : Holding Type

Blank : Normal Type(Standard)

③ Base Mateial:

Blank:Nylon66 UL94V-2

△V0:Nylon66 UL94V-0
(For 2P~8P)

④ Plated:

Blank: Tin Plated

G: Gold Plated

G1: Gold 1μ

G2: Gold Plated 30μ

⑤ PIN Length:

S1: L:15.2 mm Dip:4.4mm

S2: L:13.2mm Dip:2.5mm

/S: L:18mm Dip:7.4mm

⑥ COLOR:

Blank:Nature

BK:BLACK

BU:BLUE

⑦ DIP LENGTH:

D2: L:14.2 DIP: 2.5mm

D1: L:14.2 DIP: 3.4mm

D : L:14.2 DIP: 2.9mm

BLANK : L:14.2 DIP: 3.3mm

• Material : Contact : Brass, Tin Plated

Base : Nylon 66 UL94V-2

• Q' ty : 1000 pcs./Bag

⑤&⑦	L	Dip Length
Blank	14.2mm	3.3mm
D	14.2mm	2.9mm
D1	14.2mm	3.4mm
D2	14.2mm	2.5mm
S1	15.2mm	4.4mm
S2	13.2mm	2.5mm
/S	18mm	7.4mm

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2	2.54	5.08	11	25.40	27.94
3	5.08	7.62	12	27.94	30.48
4	7.62	10.16	13	30.48	33.02
5	10.16	12.70	14	33.02	35.56
6	12.70	15.24	15	35.56	38.10
7	15.24	17.78	16	38.10	40.64
8	17.78	20.32	17	40.64	43.18
9	20.32	22.86	18	43.18	45.72
10	22.86	25.40	19	45.72	48.26



喬訊電子工業股份有限公司
 CHYAO SHIUNN
 ELECTRONIC INDUSTRIAL LTD.

PART NO JS-6001-XX
 2.54mm Crimp Style Connectors Wafer

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞	1:1	mm	.0 ±0.30	△	變更原因遺失	邱森鴻	04/12/31	△	在表格中增加16~19pinA, B尺寸	鄭小端	14/04/21
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△	變更原因遺失	陳文松	05/07/19	△	新增V0材質選項	林宛盈	15/02/02
周家慶	⊕	a9	.000 ±0.10	△	變更原因遺失	余秀麗	05/09/28	△			
DRAWN BY	DATE	SIZE	ANGLE	△	圖面合併	林謙豪	12/01/03				
林宛盈	2015/02/02	A4	0° ±1°	△	物性表修改	林謙豪	12/05/28				
			.0° ±	△	新增產品規格	周美麗	13/02/22				
			SHEET 1/1	△	新增打內K料號及取消PA46材質	林宛盈	14/01/22				

CUSTOMER
 Conforms to The RoHS Instruction