



- SPECIFICATIONS**
- Current Rating : 3A AC/DC
  - Withstanding Voltage : 1,500V AC/minute
  - Insulation Resistance : 500MΩ min
  - Temperature Range : -25°C to +85°C
  - Contact Resistance : 10 milliohms Max.

- TERMINAL**
- Part No. : JS-6504-TX
  - ① Material: Blank : Phos. Bronze  
B : Brass
  - Applicable Wires : AWG# 22 - 28
  - Finish : Tin Plated
  - Thickness : 0.2mm
  - Q' ty : 7,000 pcs./Reel

 喬訊電子工業股份有限公司  
CHYAO SHIUNN  
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-6504-TX  
2.50mm Wire to Wire Connector

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	△	產品材質變更	林文彬	2006/12/30	△			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△	合併圖面&修改料號敘述	王誠賢	2011/07/25	△			
周慈雲		a3	.000 ±0.10	△	增加端子搖繞方向圖	吳弘文	2014/10/24	△			
DRAWN BY	DATE	SIZE	ANGLE						CUSTOMER		
吳弘文	2014/10/24	A4	0° ±1°	△					Conforms to The RoHS Instruction		
			.0° ±	△							
			SHEET 1/1	△							