



SECTION:A-A

■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max.

■ HOUSING

- Part No. : JS-8002-XX(XX)

① Poles : 2 - 15      ① ②

② Material :

Blank:Nylon 66 UL94V-2

SM:SCHULAMID (Polyamide 6 UL94V-2)

- Q' ty : 1,000 pcs./Bag

Poles	Dimensions(mm)	
	A	B
2	2.50	5.80
3	5.00	8.30
4	7.50	10.80
5	10.00	13.30
6	12.50	15.80
7	15.00	18.30
8	17.50	20.80
9	20.00	23.30
10	22.50	25.80
11	25.00	28.30
12	27.50	30.80
13	30.00	33.30
14	32.50	35.80
15	35.00	38.30



喬訊電子工業股份有限公司  
CHYAO SHIUNN  
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-8002-XX(XX)  
2.50mm Crimp Style Connectors Housing

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30								
CHECKED BY	PROJ	VER NO.	.00 ±0.20		套新圖框，刪除GP料號	張逸維	2012/11/23				
周家慶		a4	.000 ±0.10		增加模號與部分標註說明	林宛盈	2013/10/09				
DRAWN BY	DATE	SIZE	ANGLE		增加SM(舒爾曼料)選項	曾慶根	2015/10/23				
曾慶根	2015/10/23	A4	0° ±1°								
			.0° ±								
			SHEET 1/1								

CUSTOMER  
Conforms to The RoHS Instruction