



Poles	Part No.	Dimensions(mm)		Poles	Part No.	Dimensions(mm)	
		A	B			A	B
4	JS-1106-2x2	2.54	5.08	44	JS-1106-22x2	53.34	55.88
6	JS-1106-3x2	5.08	7.62	46	JS-1106-23x2	55.88	58.42
8	JS-1106-4x2	7.62	10.12	48	JS-1106-24x2	58.42	60.96
10	JS-1106-5x2	10.12	12.70	50	JS-1106-25x2	60.96	63.50
12	JS-1106-6x2	12.70	15.24	52	JS-1106-26x2	63.50	66.04
14	JS-1106-7x2	15.24	17.78	54	JS-1106-27x2	66.04	68.58
16	JS-1106-8x2	17.78	20.32	56	JS-1106-28x2	68.58	71.12
18	JS-1106-9x2	20.32	22.86	58	JS-1106-29x2	71.12	73.66
20	JS-1106-10x2	22.86	25.40	60	JS-1106-30x2	73.66	76.20
22	JS-1106-11x2	25.40	27.94	62	JS-1106-31x2	76.20	78.74
24	JS-1106-12x2	27.94	30.48	64	JS-1106-32x2	78.74	81.20
26	JS-1106-13x2	30.48	33.02	66	JS-1106-33x2	81.20	83.82
28	JS-1106-14x2	33.02	35.56	68	JS-1106-34x2	83.82	86.36
30	JS-1106-15x2	35.56	38.10	70	JS-1106-35x2	86.36	88.90
32	JS-1106-16x2	38.10	40.64	72	JS-1106-36x2	88.90	91.44
34	JS-1106-17x2	40.64	43.18	74	JS-1106-37x2	91.44	93.98
36	JS-1106-18x2	43.18	45.72	76	JS-1106-38x2	93.98	96.52
38	JS-1106-19x2	45.72	48.26	78	JS-1106-39x2	96.52	99.06
40	JS-1106-20x2	48.26	50.80	80	JS-1106-40x2	99.06	101.60
42	JS-1106-21x2	50.80	53.34				

■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000MΩ min
- Temperature Range : - 20°C to + 85°C
- Contact Resistance : 20mΩ max

■ HEADER

- Part No. : JS-1106-XXXx2 (180°)
- JS-1106-XXx2 : GP Produces
- JS-1106-0XXx2 : Non GP Produces
- Poles : 2x2-40x2 (Double Row)
- Material : Contact : Brass, Gold Plated
- Base : PBT UL94V-0
- Q' ty : 1000 pcs./Bag

PENZEL COMERCIO EXTERIO LTDA.		APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE
		林陳鏞	4:1	mm	.0	±0.3			
PART NO JS-1106-XXx2		CHECKED BY	PROJ	VER NO.	.00	±0.2			
		林勇生			.000	±0.1			
2.54mm Center Mini Latch Header		DRAWN BY	DATE	SIZE	ANGLE				
		邱森鴻	2004/12/31	A4	0°	±			
					.0°	±			