



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 250V AC /minute
- Insulation Resistance : 100M Ω min
- Temperature Range : - 40°C to + 85°C
- Contact Resistance : 20m Ω max

■ WAFER

- Part No. : JS-1147R-XXX (DIP Type)
JS-1147R-XX : GP Produces
JS-1147R-0XX : Non GP Produces
- Poles : 2-15
- Material : Contact : Brass, Tin Plated
Base : Nylon PA46 UL94V-0
- Finish : Tin Plated
- Q' ty : 1,000 pcs./PVC Box

| Poles | Part No. | Dimensions (mm) | | |
|-------|-------------|-----------------|-------|-------|
| | | A | B | C |
| 2 | JS-1147R-02 | 1.25 | 4.25 | 3.05 |
| 3 | JS-1147R-03 | 2.50 | 5.50 | 4.30 |
| 4 | JS-1147R-04 | 3.75 | 6.75 | 5.55 |
| 5 | JS-1147R-05 | 5.00 | 8.00 | 6.80 |
| 6 | JS-1147R-06 | 6.25 | 9.25 | 8.05 |
| 7 | JS-1147R-07 | 7.50 | 10.50 | 9.30 |
| 8 | JS-1147R-08 | 8.75 | 11.75 | 10.55 |
| 9 | JS-1147R-09 | 10.00 | 13.00 | 11.80 |
| 10 | JS-1147R-10 | 11.25 | 14.25 | 13.05 |
| 11 | JS-1147R-11 | 12.50 | 15.50 | 14.30 |
| 12 | JS-1147R-12 | 13.75 | 16.75 | 15.55 |
| 13 | JS-1147R-13 | 15.00 | 18.00 | 16.80 |
| 14 | JS-1147R-14 | 16.25 | 19.25 | 18.05 |
| 15 | JS-1147R-15 | 17.50 | 20.50 | 19.30 |

| | | | | | | | | |
|---|-------------|------------|---------|-----------|------|-----|-----------------|------|
| PENZEL COMERCIO EXTERIOR LTDA. | APPROVED BY | SCALE | UNIT | TOLERANCE | | LTR | REVISION RECORD | DATE |
| | 林陳鏢 | 8:1 | mm | .0 | ±0.3 | | | |
| PART NO JS-1147R-XX | CHECKED BY | PROJ | VER NO. | .00 | ±0.2 | | | |
| | 林勇生 | | | .000 | ±0.1 | | | |
| 1.25mm Crimp Style Connectors Wafer <DIP> | DRAWN BY | DATE | SIZE | ANGLE | | | | |
| | 邱森鴻 | 2004/12/31 | A4 | 0° | ± | | | |
| | | | | .0° | ± | | | |