



■ SPECIFICATIONS

- Voltage Rating : 125V AC/DC
- Current Rating : 1A (Max) AC/DC
- Withstanding Voltage : 125V AC /minute
- Insulation Resistance : 100MΩ min
- Temperature Range : - 40°C to + 85°C
- Contact Resistance : 20mΩ max

■ WAFER

- Part No. : JS-1147V-XXX (SMT Type)
JS-1147V-XX : GP Produces
JS-1147V-0XX : Non GP Produces
- Poles : 2 - 15
- Material : Contact : Brass, Tin Plated
Base : Nylon PA46 UL94V-0
- Finish : Tin Plated
- Q' ty : 1,000 pcs./Tape & Reel

Poles	Part No.	Dimensions (mm)				
		A	B	C	D	E
2	JS-1147V-02	1.25	4.25	3.05	7.65	7.25
3	JS-1147V-03	2.50	5.50	4.30	8.90	8.50
4	JS-1147V-04	3.75	6.75	5.55	10.15	9.75
5	JS-1147V-05	5.00	8.00	6.80	11.40	11.00
6	JS-1147V-06	6.25	9.25	8.05	12.65	12.25
7	JS-1147V-07	7.50	10.50	9.30	13.90	13.50
8	JS-1147V-08	8.75	11.75	10.55	15.15	14.75
9	JS-1147V-09	10.00	13.00	11.80	16.40	16.00
10	JS-1147V-10	11.25	14.25	13.05	17.65	17.25
11	JS-1147V-11	12.50	15.50	14.30	18.90	18.50
12	JS-1147V-12	13.75	16.75	15.55	20.15	19.75
13	JS-1147V-13	15.00	18.00	16.80	21.40	21.00
14	JS-1147V-14	16.25	19.25	18.05	22.65	22.25
15	JS-1147V-15	17.50	20.50	19.30	23.90	23.50

PENZEL COMERCIO EXTERIOR LTDA.	APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE
	林陳鏢	5:1	mm	.0	±0.3			
	CHECKED BY	PROJ	VER NO.	.00	±0.2	ECR	200509-005	2005/09/21
				.000	±0.1			
PART NO	JS-1147V-XX		SIZE	ANGLE				
1.25mm Crimp Style Connectors Wafer <SMT>	陳文松	2005/09/21	A4	0°	±			
				.0°	±			