



■ SPECIFICATIONS

- Voltage Rating : 100 V AC/DC
- Current Rating : 0.5A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 500MΩ min
- Temperature Range : - 40°C to + 85°C
- Contact Resistance : 20mΩ max

■ FFC/FPC CONNECTOR (SMT Type)

- Part No. : JS-1157U (R/A, Top Contact Style)
- Poles : 4 - 34
- Material : Contact : Phos. Bronze, Tin Plated
Base : PPS UL94V-0
- Q'ty : 1,500 pcs./Tape & Reel

Poles	Part No.	Dimensions (mm)			
		A	B	C	D
4	JS-1157U- 4	9.85	3.00	11.00	5.05
5	JS-1157U- 5	10.85	4.00	12.00	6.05
6	JS-1157U- 6	11.85	5.00	13.00	7.05
7	JS-1157U- 7	12.85	6.00	14.00	8.05
8	JS-1157U- 8	13.85	7.00	15.00	9.05
9	JS-1157U- 9	14.85	8.00	16.00	10.05
10	JS-1157U-10	15.85	9.00	17.00	11.05
11	JS-1157U-11	16.85	10.00	18.00	12.05
12	JS-1157U-12	17.85	11.00	19.00	13.05
13	JS-1157U-13	18.85	12.00	20.00	14.05
14	JS-1157U-14	19.85	13.00	21.00	15.05
15	JS-1157U-15	20.85	14.00	22.00	16.05
16	JS-1157U-16	21.85	15.00	23.00	17.05
17	JS-1157U-17	22.85	16.00	24.00	18.05
18	JS-1157U-18	23.85	17.00	25.00	19.05
19	JS-1157U-19	24.85	18.00	26.00	20.05
20	JS-1157U-20	25.85	19.00	27.00	21.05
21	JS-1157U-21	26.85	20.00	28.00	22.05
22	JS-1157U-22	27.85	21.00	29.00	23.05
23	JS-1157U-23	28.85	22.00	30.00	24.05
24	JS-1157U-24	29.85	23.00	31.00	25.05
25	JS-1157U-25	30.85	24.00	32.00	26.05
26	JS-1157U-26	31.85	25.00	33.00	27.05
27	JS-1157U-27	32.85	26.00	34.00	28.05
28	JS-1157U-28	33.85	27.00	35.00	29.05
29	JS-1157U-29	34.85	28.00	36.00	30.05
30	JS-1157U-30	35.85	29.00	37.00	31.05
31	JS-1157U-31	36.85	30.00	38.00	32.05
32	JS-1157U-32	37.85	31.00	39.00	33.05
33	JS-1157U-33	38.85	32.00	40.00	34.05
34	JS-1157U-34	39.85	33.00	41.00	35.05

1.00mm FFC/FPC ZIF SMT type connectors-Single beam contact style			PENZEL COMERCIO EXTERIOR LTDA.			TOLERANCE	
ECR	200307-004	2003/07/15	APPROVED BY	DATE	SCALE	.0	±0.30
				2003/07/17	3:1	.00	±0.20
			CHECKED BY	UNIT		.000	±0.10
				mm		PART NO	
			DRAWN BY	VER NO.	SIZE	JS-1157U-XX	
LTR	REVISION RECORD	DATE		B1	A4		