



### ■ SPECIFICATIONS

- Voltage Rating : 100 V AC/DC
- Current Rating : 0.5A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 500M  $\Omega$  min
- Temperature Range : - 40°C to + 85°C
- Contact Resistance : 20m  $\Omega$  max

### ■ FFC/FPC CONNECTOR (SMT Type)

- Part No. : JS-1157V (Straight)
- Poles : 4 - 34
- Material : Contact : Phos. Bronze, Tin Plated  
Base : PPS UL94V-0
- Q' ty : 800 pcs./Tape & Reel

Poles	Part No.	Dimensions (mm)			
		A	B	C	D
4	JS-1157V-4	9.20	3.00	11.00	5.05
5	JS-1157V-5	10.20	4.00	12.00	6.05
6	JS-1157V-6	11.20	5.00	13.00	7.05
7	JS-1157V-7	12.20	6.00	14.00	8.05
8	JS-1157V-8	13.20	7.00	15.00	9.05
9	JS-1157V-9	14.20	8.00	16.00	10.05
10	JS-1157V-10	15.20	9.00	17.00	11.05
11	JS-1157V-11	16.20	10.00	18.00	12.05
12	JS-1157V-12	17.20	11.00	19.00	13.05
13	JS-1157V-13	18.20	12.00	20.00	14.05
14	JS-1157V-14	19.20	13.00	21.00	15.05
15	JS-1157V-15	20.20	14.00	22.00	16.05
16	JS-1157V-16	21.20	15.00	23.00	17.05
17	JS-1157V-17	22.20	16.00	24.00	18.05
18	JS-1157V-18	23.20	17.00	25.00	19.05
19	JS-1157V-19	24.20	18.00	26.00	20.05
20	JS-1157V-20	25.20	19.00	27.00	21.05
21	JS-1157V-21	26.20	20.00	28.00	22.05
22	JS-1157V-22	27.20	21.00	29.00	23.05
23	JS-1157V-23	28.20	22.00	30.00	24.05
24	JS-1157V-24	29.20	23.00	31.00	25.05
25	JS-1157V-25	30.20	24.00	32.00	26.05
26	JS-1157V-26	31.20	25.00	33.00	27.05
27	JS-1157V-27	32.20	26.00	34.00	28.05
28	JS-1157V-28	33.20	27.00	35.00	29.05
29	JS-1157V-29	34.20	28.00	36.00	30.05
30	JS-1157V-30	35.20	29.00	37.00	31.05
31	JS-1157V-31	36.20	30.00	38.00	32.05
32	JS-1157V-32	37.20	31.00	39.00	33.05
33	JS-1157V-33	38.20	32.00	40.00	34.05
34	JS-1157V-34	39.20	33.00	41.00	35.05

1.00mm FFC/FPC ZIF SMT type connectors-Single beam contact style			PENZEL COMERCIO EXTERIOR LTDA.			TOLERANCE	
ECR	200307-004	2003/07/15	APPROVED BY	DATE	SCALE	.0	±0.30
			林陳樂	2003/07/17	3:1	.00	±0.20
			CHECKED BY	UNIT		.000	±0.10
			林勇生	mm		PART NO	
			DRAWN BY	VER NO.	SIZE	JS-1157V-XX	
LTR	REVISION RECORD	DATE	邱森鴻	B1	A4		