



■ SPECIFICATIONS

- Voltage Rating : 50V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 100M Ω min
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m Ω max

■ TERMINAL

- Part No. : JS-1253-XT, JS-1253-XTG
JS-1253-T, JS-1253-TG : GP Produces
JS-1253-0T, JS-1253-0TG : Non GP Produces
- Applicable Wires : AWG # 28 - 32
- Material : Phos. Bronze
- Finish : Tin Plated, Gold Plated
- Thickness : 0.15 mm
- Q' ty : 20,000 pcs./Reel

PENZEL COMERCIO EXTERIOR LTDA.

APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE
			.0	± 0.3			
林陳鏞	6:1	mm	.00	± 0.2			
CHECKED BY	PROJ	VER NO.	.000	± 0.1			
林勇生		a	ALL	\pm			
DRAWN BY	DATE	SIZE	ANGLE				
邱森鴻	2004/12/31	A4	0 $^{\circ}$	\pm			
			.0 $^{\circ}$	\pm			

PART NO JS-1253-T;JS-1253-TG

1.00mm Crimp Style connectors Terminal <SMT>