



P.C.B LAYOUT

SPECIFICATIONS
 Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: PBT30%GF,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C3030WR-F-2X1P	---	6.65
C3030WR-F-2X2P	3.00	9.65
C3030WR-F-2X3P	6.00	12.65
C3030WR-F-2X4P	9.00	15.65
C3030WR-F-2X5P	12.00	18.65
C3030WR-F-2X6P	15.00	21.65
C3030WR-F-2X7P	18.00	24.65
C3030WR-F-2X8P	21.00	27.65
C3030WR-F-2X9P	24.00	30.65
C3030WR-F-2X10P	27.00	33.65
C3030WR-F-2X11P	30.00	36.65
C3030WR-F-2X12P	33.00	39.65

PENZEL COMERCIO EXTERIOR LTDA.			TITLE:
UNIT	SCALE	SHEET	1 OF 1
DRAWN BY	APPROVED BY	3.00mm PITCH	
2001.02.01	2001.02.01	90° WAFER,	
GENERAL TOLERANCE			MICRO-FIT
X. X40.25	ANG.PE	DRAW NO.:	
X. XX40.15		C3030WR-F-2XNP	
X. XXX40.05		REV.	B0
REV.	DISCUSSION	DATE	2005.12.14
B0	NEW RELEASE		