



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 7A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max

■ HOUSING

- Part No. : JS-5001-XXX  
 JS-5001-XX : GP Produces  
 JS-5001-0XX : Non GP Produces
- Poles : 2-14
- Material : Nylon 66 UL94V-2
- Q' ty : 1,000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-5001-02	3.96	8.92
3	JS-5001-03	7.92	12.88
4	JS-5001-04	11.88	16.84
5	JS-5001-05	15.84	20.80
6	JS-5001-06	19.80	24.76
7	JS-5001-07	23.76	28.72
8	JS-5001-08	27.72	32.68
9	JS-5001-09	31.68	36.64
10	JS-5001-10	35.64	40.60
11	JS-5001-11	39.60	44.56
12	JS-5001-12	43.56	48.52
13	JS-5001-13	47.52	52.48
14	JS-5001-14	51.48	56.44

PENZEL COMERCIO EXTERIOR LTDA.	APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE
	林陳鏢	3:1	mm	.0	±0.3			
PART NO JS-5001-XX	CHECKED BY	PROJ	VER NO.	.00	±0.2			
	林勇生	⊕ □	□	.000	±0.1			
3.96mm Crimp Style Connectors Housing	DRAWN BY	DATE	SIZE	ANGLE				
	邱森鴻	2004/12/31	A4	0°	±			
				.0°	±			